

CANMORE SYN 2-STROKE ENGINE OIL

FEATURES & BENEFITS

- Ensures higher engine protection, limits deposits on pistons and segments
- Pours easily at temperatures as low as -38°C
- Prevents rust and corrosion, minimizes ring-sticking, port plugging and pre-ignition
- Less fumes escape
- Releases a pleasant vanilla scent

CANMORE SYN 2-STROKE is a synthetic blend lubricant for 2-stroke engines. The synthetic components improve lubricity while providing cooler and more efficient combustion resulting in reduction of smoke which prevents exhaust port deposits and blockage. It has been formulated with snowmobiles in mind, both air and liquid-cooled where the manufacturer recommends a low-ash oil. It meets the stringent requirements of Bombardier® snowmobiles and its power valve optimized. Formulated to provide superior protection for high-performance 2-stroke engines.

CANMORE SYN 2-STROKE prevents deposits on pistons, thereby providing a higher level of lubrication and reducing wear and failure. You can increase the lifespan of your engine and have better protection under heavy loads and high temperatures with this premium oil. Enjoy your ride with reduced smoke emissions and a pleasant vanilla scent.

CANMORE SYN 2-STROKE can be used in oil-injected or pre-mixed systems with a ratio of up to 100:1. This oil is suitable for chain saws, including professional models, as well as string trimmers, lawnmowers, snow blowers, motorcycles, ATVs and any other air-cooled 2-stroke gasoline engine. For water-cooled outboard engines, consider using **CANMORE PREMIUM 2-STROKE ENGINE OIL**.

SIZES

CANMORE SYN 2-STROKE
946 ml

MEETS OR EXCEEDS

- JASO FB, FC, FD
- ISO-L-EGB, EGC, EGD
- API TC

MEETS THE REQUIREMENTS OF MANUFACTURERS INCLUDING:

Bombardier
Arctic Cat
Polaris
Yamaha

TYPICAL RESULTS

GRADE	CANMORE SYN 2-STROKE
VISCOSITY (D-445) cSt @ 40 °C cSt @ 100 °C	53.2 8.5
VISCOSITY INDEX (D2270)	135
POUR POINT (°C) (D97)	-40
FLASH POINT (°C) (D92)	99
DENSITY @ 15°C (ASTM D4052) kg/L	0.87

