

CANMORE PREMIUM 2-STROKE ENGINE OIL

FEATURES & BENEFITS

- Ashless formulation.
- Suitable for premix and oil injection systems.
- Specially formulated for outboards and other liquid cooled 2-stroke engines.
- Suitable for use in all 2-T DFI (Dual Fuel Injected).
- Outboard engines ex. E-Tec, Opitec, HPDI etc.
- Superior deposit control.
- Extends spark plug life.
- Excellent rust and corrosion protection.
- Pre-mixes easily, even in winter temperatures.

CANMORE PREMIUM 2-STROKE is a premium lubricant for water-cooled outboard 2-stroke gasoline engines. It uses highly refined base oil for its low carbon-forming tendency, along with ashless performance additives and a solvent to improve mixing with gasoline.

CANMORE PREMIUM 2-STROKE is suitable for both pre-mix and modern oil injection systems. It has a distinctive blue colour to provide positive confirmation that the oil has been pre-mixed into the gasoline. The ashless formulation provides for clean pistons and cylinders while minimizing deposits that can cause ring-sticking, port-plugging and pre-ignition. It also effectively prevents rust and corrosion, which is very important in the humid environment of outboard engines.

CANMORE PREMIUM 2-STROKE is recommended wherever the manufacturer recommends an NMMA® (National Marine Manufacturers Association) approved lubricant, meeting the current performance standard for such oils, TC-W3®. Tests by engine manufacturers have shown that this oil, when compared to oils of the previous TC-WII category, doubles the life of the power-head.

CANMORE PREMIUM 2-STROKE is also recommended for use in snowmobile engines, whether liquid or air-cooled, where the manufacturer recommends an NMMA® approved or TC-W type lubricant. For heavy-duty, air-cooled, 2-stroke gasoline engines, we recommend using **CANMORE 2-STROKE ENGINE OIL**.

*NMMA : National Marine Manufacturers Association.

TYPICAL RESULTS

GRADE	CANMORE PREMIUM 2-STROKE
VISCOSITY (D-445) cSt @ 40 °C cSt @ 100 °C	27.6 6.2
VISCOSITY INDEX (D2270)	185
POUR POINT (°C) (D97)	-48
FLASH POINT (°C) (D92)	54.4
SULPHATED ASJ (D874)	0.0
TOTAL BASE NUMBER	8.4
SOLVENT %wt	32
BROOKFIELD VISCOSITY (D2983) @ -25 °C (cP) @ -40 °C (cP)	1260 10,100

SIZES

CANMORE PREMIUM 2-STROKE
946 ml

