

CANMORE 2-STROKE ENGINE OIL

FEATURES & BENEFITS

- Economical.
- Good low temperature fluidity.
- Good film strength at high temperature.
- Will not stain pistons.
- Provides excellent cleanliness.
- Low ash formulation.
- Distinct blue identifying color.

CANMORE 2-STROKE was developed for the professional user where high performance and equipment reliability is a must.

CANMORE 2-STROKE is designed to take on the demanding requirements ultra-high performance racing and general-purpose air-cooled 2-stroke gasoline engines used in power equipment and recreational vehicles. The unique concentrations of detergent and anti-wear additives have a low ash level to prevent crankcase, piston, and ring groove deposits that lead to poor performance. Fuel oxidation stability is improved to reduce varnish and gumming.

CANMORE 2-STROKE is a high performance mineral based lubricant for enhanced performance over straight conventional products. It is formulated to help improve lubricity while providing cooler and more efficient combustion resulting in reduction of smoke which prevents exhaust port deposits and blockage.

CANMORE 2-STROKE is recommended for all 2-stroke lubrication systems, whether pre-mix or oil injected lubrication, except water-cooled outboards, where non-ash 2-stroke oils are required. In those applications, use **CANMORE PREMIUM 2-STROKE ENGINE OIL**.

CANMORE 2-STROKE is suitable for chain saws, including professional models, as well as string trimmers, lawnmowers, snow blowers, motorcycles, ATVs and any other air-cooled 2-stroke gasoline engines. It is also suitable for snowmobile 2-stroke engines, whether air or liquid-cooled, where the manufacturer recommends a low-ash, JASO FD, ISO-L-EGD, or API TC oil. In particular, it meets the demanding requirements of Bombardier snowmobiles.

MEETS OR EXCEEDS

- JASO FB, FC, FD
- ISO-L-EGB, EGC, EGD
- API TC

TYPICAL RESULTS

GRADE	CANMORE 2-STROKE ENGINE OIL
VISCOSITY (D-445) cSt @ 40 °C cSt @ 100 °C	54.6 8.0
VISCOSITY INDEX (D2270)	114
POUR POINT (°C) (D97)	-36
FLASH POINT (°C) (D92)	97
DENSITY @ 15°C (ASTM D4052) kg/L	0.8727

SIZES

CANMORE 2-STROKE ENGINE OIL
946 ml

