

CANMORE UNIVERSAL ANTIFREEZE-COOLANT 50/50 PRE MIXED

FEATURES & BENEFITS

- Compatible with heavy duty diesel engines with SCA
- Service life is 80,000km (50,000 miles) or two years between changes if used after a complete drain, flush and fill.
- Protects all coolant system metals, including aluminum

CANMORE UNIVERSAL ANTIFREEZE COOLANT 50/50 is a traditional green colored coolant recommended for the cooling systems of older makes and models of foreign and domestic passenger vehicles, light duty trucks and SUV's. Formulated using high quality ethylene glycol coupled with a low silicate additive technology to prevent corrosion and pitting caused by cavitation.

CANMORE UNIVERSAL ANTIFREEZE COOLANT 50/50 provides excellent protection against temperature extremes and boil-over when used in accordance with OEM and product manufacturer's guidelines regarding product dilution.

TYPICAL RESULTS

GRADE	CANMORE UNIVERSAL ANTIFREEZE COOLANT 50/50
COLOUR	GREEN
SPECIFIC GRAVITY (15.6°C / 60°F) (D1122I)	1.08-1.09
FREEZE POINT (D1177)	-37°C / -34°F
pH (D1287)	10-11
FOAM VOLUME (mL) (D1881)	150 max.
FOAM BREAK TIME (sec) (D1881)	5 max.
RESERVE ALKALINITY (mL) (D1221)	3.4 min.
GLYCOL CONTENT (wt.%)	46 min.
INHIBITORS & WATER (wt.%)	54 max.
CHLORIDE (ppm) (D3634)	25 max.
SILICON (ppm) (D6130)	250 max.

MEETS OR EXCEEDS

- ASTM D3306
- ASTM D4985
- GM 1825M, 1899M
- Ford ESE-M97B44-A
- Chrysler MS7170
- TMC RP 302B

SIZES

CANMORE UNIVERSAL ANTIFREEZE COOLANT 50/50

4 Litre

