

CANMORE ATF DEX-III AUTOMATIC TRANSMISSION FLUID

CANMORE ATF DEX-III is a premium product specially formulated for use in automatic transmissions manufactured in 2005 and earlier General Motors, Ford, and Chrysler vehicles requiring DEXRON®, II, III (GM) and MERCON® (FORD) fluid. **CANMORE ATF DEX-III** provides excellent lowtemperature fluidity as well as good viscosity at temperatures in excess of 149°C for bearing and gear lubrication.

CANMORE ATF DEX-III has excellent corrosion and foam prevention properties. **CANMORE ATF DEX-III** meets specifications by Allison as a type C-4 fluid and it can also be used in Ford model C-6 automatic transmissions built on or after 1977 and with all Ford automatic transmissions built on or after 1980. **CANMORE ATF DEX-III** is a true multi-graded fluid and therefore can replace hydraulic oils of standard grades 15, 22, 32 and 46.

Not recommended for Ford transmissions requiring specific "Type F" or MERCON® V or GM DEXRON® VI.

TYPICAL RESULTS

GRADE	CANMORE ATF DEX-III
COLOUR	RED
DENSITY @ 15°C(ASTM D4052) kg/L	0.860
VISCOSITY (D445) cSt @ 40°C	33.8
VISCOSITY (D445) cSt @ 100°C	7.1
VISCOSITY INDEX (D2270)	177
POUR POINT (°C) (D97)	-45
FLASH POINT (°C) (D92)	213
BROOKFIELD VISCOSITY (D2983) (°C) cP@ -40°C	14000
USEFUL OPERATING TEMPERATURE RANGE* (°C)	-16/74

FEATURES & BENEFITS

- GM DEXRON® III H, G and DEXRON® II
- Allison C3 & C-4
- FORD MERCON®
- Caterpillar TO-2
- MAZDA ATF F-1
- VICKERS M2950-S I-286-5
- Volvo CE 97340



SIZES

CANMORE ATF DEX-III
1 Litre
5 Litre
18.9 Litre
205 Litre
BULK

