

## CANMORE ATF F AUTOMATIC TRANSMISSION FLUID

**CANMORE ATF F** is a niche ATF developed specifically to meet the needs of Ford vehicles manufactured between 1950 and 1980. It was formally approved by Ford for specifications M2C33. This fluid can also be used in power steering and hydraulic systems, especially in off road construction and agricultural systems.

**CANMORE ATF F** through extensive testing has demonstrated dependable performance in the laboratory and the field includes the following industry tests:

- Bench Testing
- Clutch Friction Test
- Cycling Test
- Oxidation Testing
- Vickers Pump Testing

### TYPICAL RESULTS

GRADE	CANMORE ATF F
COLOUR	RED
VISCOSITY (D445) cSt @ 40 °C	35.6
cSt @ 100 °C	7.4
VISCOSITY INDEX (D2270)	181
DENSITY @ 15°C (D4052), Kg/L	0.8659
FLASH POINT (°C) (D93)	181
POUR POINT (°C) (D97)	-41

### FEATURES & BENEFITS

- Corrosion & rust prevention.
- Anti-foam characteristics.
- Anti-wear.
- Seal swell compatibility.
- Low temperature viscosity.
- Sludge resistance.
- Meets the following: Volvo 97330, Ford M2C33-F.
- Specified for the service fill in the following passenger car manufacturers: Austin-Morris, Saab, Daihatsu, Toyo Kogyo, Ford, Toyota, Jaguar, Triumph, Rover, Volvo.

### SIZES

CANMORE ATF F
1 Litre
5 Litre
18.9 Litre
205 Litre
BULK

