

CANMORE MV MULTI-VEHICLE TRANSMISSION FLUID

CANMORE MV was designed to meet the performance requirements of global transmissions from North American, European and Asian transmission manufacturers. **CANMORE MV** offers excellent fluidity at low temperatures allowing for better lubrication and faster start-times in extremely cold temperatures.

CANMORE MV protects better and longer than previous automatic transmission fluids to reduce wear and extend the durability of the transmission. The friction properties ensure smoother, shutter-free shifting and eliminates vibration within the clutch, even when speed shifting. **CANMORE MV** may also be used as a hydraulic or power steering fluid. Please see **CANMORE MV** quick reference guide for a complete list of compatibilities.

TYPICAL RESULTS

GRADE	CANMORE MV
COLOUR	RED
(VISCOSITY (D445) cSt @ 40°C cSt @ 100°C	34.0 7.6
VISCOSITY INDEX (D2270)	202
DENSITY @ 15 °C (D4052) KG/L	0.854
BROOKFIELD VISCOSITY (D2983) cP @ -40°C	9,580
VISCOSITY (D-445) cSt @ 100 °C	6.0
POUR POINT (°C) (D97)	49
FLASH POINT (°C) (D-92)	214

FEATURES & BENEFITS

- Exceptional low temperature fluidity.
- Excellent resistance to degradation due to heat and oxidation.
- Eliminates slippage and shudder.
- Extends integrity and operational life of critical components.
- MERCON®V approved.
- Suitable for use where DEXRON® IIIH, IIIG, IIE or II is recommended.

SIZES

CANMORE MV
1 Litre
5 Litre
18.9 Litre
205 Litre
BULK



CANMORE MV MULTI-VEHICLE TRANSMISSION FLUID

Always consult your owners manual for verification of fluid type and grade!
MEETS OR EXCEEDS THE FOLLOWING INDUSTRY STANDARDS:

HIGH VISCOSITY SPECIFICATIONS

- Acura ATF-Z1
- Aisin Warner JWS 3309 (T-IV)
- Allison C-3 & C-4
- American Motors ATF +3 (MS7176-E), ATF +4 (MS9602)
- ATF RED1, RED 1K
- Audi 5 HP LT71141 (ZF 5 HP 18FL/19FL/24A)
- Audi G 052 162-A1/A2
- Audi G 055 025 A2 (JWS 3309)
- BMW JWS 3309 (T-IV)
- BMW LA2634
- BMW 7045E
- BMW ETL-8072B
- BMW MINI
- CAT TO-2
- Chrysler ATF+, +2, +3 (MS 7176E), +4 (MS 9602)
- Chrysler / Dodge MOPAR AS 68 RC (T-IV) JWS3309
- Daewoo LT 71141
- Daihatsu AMMIX ATF D-II
- Daihatsu AMMIX ATF D-III SP
- Esso LT 71141
- FIAT T-IV type, JWS 3309
- Ford MERCON
- Ford MERCON V
- Ford FNR5
- Ford M2C138CJ
- Ford M2C166H
- Ford M2C 138CJ, 166H
- Ford WSS M2C 922A1, 924A (XT-8-QAW) JWS 3309
- Fuso ATF-II
- Fuso ATF-SPII
- Fuso ATF-A4
- GM9986195 (Aisin AW, JWS 3309)
- GM TASA
- GM DEXRON II
- GM DEXRON IID
- GM DEXRON IIE
- GM DEXRON IIIG
- GM DEXRON IIHH
- Hino Blue ribbon ATF
- Honda ATF-Z1 (except in CVTs)
- Hyundai/Kia SP-III
- Hyundai/Kia Dex-II/SP-II
- Hyundai/Kia JWS 3314
- Hyundai/Kia JWS9683
- ISUZU BESCO ATF-II
- ISUZU BESCO ATF-III
- Jaguar ATF 3403 M115, ATF 3403-M115
- JASO M315-2013 1A
- JASO M315-2013 2A
- JEEP ATF+3, +4
- Lexus JWS 3309
- KIA ATF SP-II, SP-III, SP-IV, SP-IVM, Red1
- Mazda ATF D-II
- Mazda ATF M-III
- Mazda ATF M-V
- Mazda ATF F-1
- Mazda ATF S-1
- Mazda ATF N-1
- MAZDA ATF 3317
- MB 236.1
- MB 236.2
- MB 236.3
- MB 236.5
- MB 236.6
- MB 236.7
- MB 236.9
- MINI COOPER T-IV
- Mitsubishi Diaqueen SK
- Mitsubishi Diaqueen SP-II
- Mitsubishi Diaqueen SP-III
- Mitsubishi Diaqueen AW
- Mitsubishi Diaqueen J2
- NAG 1 (Chrysler, Jeep, Cherokee)
- Nissan Matic Fluid C
- Nissan Matic Fluid D
- Nissan Matic Fluid J
- Nissan Matic Fluid K
- Opel (all vehicles)
- Porsche T-IV (JWS 3309)
- Saab T-IV (JWS 3309)
- Saturn T-IV (JWS 3309)
- Scion (all vehicles)
- Subaru ATF
- Subaru ATF 5AT
- Subaru DEXRON -II
- Subaru ATF, ATF HP
- Suzuki AT OIL 5006
- Suzuki ATF 2326
- Suzuki ATF 2384K
- Suzuki JWS 3309
- Suzuki ATF 3314
- Suzuki ATF 3317
- Texaco 7045-E
- Texaco 8072B
- Texaco N402
- Toyota ATF D-II
- Toyota ATF D-III
- Toyota ATF T-III
- Toyota ATF T-IV
- Vickers M2950-S, I-286-S
- Volvo CE 97340
- VW G-055-025 A2 (JWS 3309)
- ZF TE-ML 09
- ZF TE-ML 11A, 11B



CANMORE Petroleum

205-2415 Holly Lane,
Ottawa Ontario K1V 7P2, Canada
www.canmorepetroleum.com

1-613 800 1214

CANMORE

CANMORE MV MULTI-VEHICLE TRANSMISSION FLUID

Always consult your owners manual for verification of fluid type and grade!

MEETS OR EXCEEDS THE FOLLOWING INDUSTRY STANDARDS:

LOW VISCOSITY SPECIFICATIONS

- Honda DW-1
- Hyundai/Kia SP-IV
- Hyundai/Kia SP-IV M
- Hyundai/Kia SP-IV RR
- JWS 3324 (WS)
- Mazda ATF FZ
- Mitsubishi Diaqueen SP-IV
- Mitsubishi Diaqueen J3
- Mitsubishi Diaqueen ATF PA
- Nissan Matic Fluid S
- Saab 93 165 147
- Toyota ATF WS

POWER STEERING APPLICATIONS

- Chrysler MS-1872
- Chrysler MS 5931
- Chrysler MS 9602
- Ford M2C195-A
- GM P/N 89021184
- GM P/N 1052884 (GM 9985010)
- GM P/N 12345866 (GM 9985835)
- Hyundai/Kia PSF-3
- Mercedes-Benz 236.3 (P/N 000 989 88 03)
- Mitsubishi PS fluid, Diamond SP-III
- Nissan PSF-II
- Saab P/N 45 30 09 800
- Subaru P/N K0209A0080
- ZF TE-ML 09

TRANSFER CASE APPLICATIONS

- Ford Mercon V
- Ford Part#XL-12
- GM IID, IIH

You should always consult your Owners Manual when selecting any lubricant product. Check with your sales Representative for latest product approvals. Please note, these are typical performance indicators and can change without notice.

CANMORE Petroleum
205-2415 Holly Lane,
Ottawa Ontario K1V 7P2, Canada
www.canmorepetroleum.com

1-613 800 1214

