

CANMORE HDD MONOGRADE CONVENTIONAL MOTOR OIL CONVENTIONAL 40 AND 50 CF/CF-2 SF

CANMORE HDD Monograde Conventional 40 AND 50 CF/CF-2 SF are blended from select high viscosity base stocks and low-ash additives with sufficient detergent to ensure excellent engine cleanliness, minimize ring-sticking, reduced liner-scuffing, prevents sludge formation, reduces bearing corrosion and cuts back on engine rusting. **CANMORE HDD Monograde Conventional 40 AND 50 CF/CF-2 SF** were developed to meet the needs of mixed fleet operators in order to reduce inventory. **CANMORE HDD Monograde Conventional 40 AND 50 CF/CF-2 SF** can be used in high speed diesel engines in automotive, construction and certain marine diesel applications.

CANMORE HDD Monograde Conventional 40 AND 50 CF/CF-2 SF is compatible for the recommended Detroit Diesel 2-cycle engines. **CANMORE HDD Monograde Conventional 40 AND 50 CF/CF-2 SF** can also be used as hydraulic oils where appropriate as long as care is taken not to mix them with regular hydraulic oils.

TYPICAL RESULTS

GRADE	40	50
Specific Gravity (D-4502)@15°C, kg/l	0.8941	0.8996
Viscosity Index (D-2270)	101	101
Pour Point (°C) (D-97)	-23	-16
Flash Point (°C) (D-92)	204	202
Viscosity (D-445)@ 40°C, cSt	141.3	216.4
Viscosity (D-445)@ 100°C, cSt	14.5	19.3
Total Base Number (D-2896)	7.7	7.7

MEETS OR EXCEEDS

- API CF/CF2,
- CAT TO2 (40, 50),
- Detroit Diesel 7SE270 (40)

FEATURES & BENEFITS

- High viscosity/low ash formulations
- Promotes engine cleanliness
- Excellent resistance to high temperature
- Meets requirements of API CF / CF-2
- Low ash less than 1%
- Suitable for truck manual transmissions (SAE 50)

SIZES

40	50
1 Litre	1 Litre
4 Litre	4 Litre
5 Litre	5 Litre
18.9 Litre	18.9 Litre
205 Litre	205 Litre
1000 Litre	1000 Litre

