



CANMORE HDD FULL SYNTHETIC MOTOR OIL

SYNTHETIC 0W-40

Canada, one of the harshest cold temperature climates in the world, requires an engine oil that delivers exceptional cold temperature properties such as exceptional cold cranking and cold pumping ability. Performance in these areas enable faster startup and wear protection when the engine is most vulnerable.

CANMORE HDD Full Synthetic 0W-40 diesel motor oil combines an unique formula of Polyalphaolefin (PAO) synthetic group IV base oils together with a high quality performance additive package. This advanced heavy-duty diesel motor oil is specially formulated to deliver exceptional cold temperature performance for the most demanding operating conditions.

CANMORE HDD Full Synthetic 0W-40 is based on the same high performance API CK-4 performance additive technology used for **CANMORE HDD Full Synthetic 15W-40 & 10W-30**. The advanced formulation is designed for use in exhaust after treatment devices found in current emissions-compliant on and off-road equipment. It is **suitable for use** in manufacturer's (Detroit Diesel, Cummins, Mack, Renault, and Volvo) most advanced engines as well as older, pre-2007 engines.

This product is fully backed by CANMORE's quality guarantee in applications where "CK-4 0W-40" is specified by the equipment manufacturer.

FEATURES & BENEFITS

- 100% Synthetic
- Advanced formulation
- Exceptional in cold weather

SIZES

0W-40
5 Litre
18.9 Litre
205 Litre
1000 Litre

TYPICAL RESULTS

GRADE	0W-40
VISCOSITY (D445) cSt @ 40 °C cSt @ 100 °C	98 14.9
VISCOSITY INDEX (D2270)	171
DENSITY (D4502) @15°C (kg/l)	0.8500
POUR POINT (°C) (D97)	-52
FLASH POINT (°C) (D92)	204
TOTAL BASE NUMBER (D2896)	10.4



You should always consult your Owners Manual when selecting any lubricant product. Check with your sales Representative for latest product approvals. Please note, these are typical performance indicators and can change without notice.

CANMORE Petroleum
205-2415 Holly Lane,
Ottawa Ontario K1V 7P2, Canada
www.canmorepetroleum.com

1-613 800 1214