

CANMORE PCG CONVENTIONAL MOTOR OIL HIGH PERFORMANCE MOTOR OIL



CANMORE PCG CONVENTIONAL is a motor oil that has been developed to exceed the highest qualifications and specifications of the North American motor industry. **CANMORE PCG CONVENTIONAL** performs above the standard requirements of the American Petroleum Institute's (API) highest performance level SN, as well as the latest ILSAC GF-5 requirements for warranty of the latest models by all domestic automobile manufacturers.

CANMORE PCG CONVENTIONAL API performance is measured in actual engines under controlled conditions that require dismantling of engines after each test to attain accurate measurements on wear, deposits and the condition of the oil. **CANMORE PCG CONVENTIONAL** grades are suitable for even the most severe driving situations including inner city delivery services, taxis and police cars. Whether you are stop-and-go city driving, short trips in cold weather or towing a trailer in the summer, **CANMORE PCG CONVENTIONAL** has the right fit for your needs.

CANMORE PCG CONVENTIONAL 5W-20, 5W-30 and 10W-30 are qualified for warranty service in new vehicles, as indicated by the ILSAC GF-5 rating and "starburst" symbol on bottle labels.

FEATURES & BENEFITS

- ILSAC GF-5 qualified (5W-20, 5W-30, and 10W-30).
- Resource conserving rating (5W-20, 5W-30, and 10W-30).
- Formulated for Ford, Honda, Toyota, & Mazda vehicles (5W-20).
- Enhanced oil durability for longer service life.
- Improved fuel economy over the entire life of the oil.
- Reduces engine deposits, varnish and sludge formation.
- Combats corrosion and moisture in ethanol blended fuels.
- Outstanding resistance to viscosity breakdown.
- Maximum wear protection.
- Improved oxidation resistance.
- Excellent cold weather performance.

TYPICAL RESULTS

SAE GRADE	5W-20	5W-30	10W-30	10W-40	20W-50
DENSITY @ 15°C (ASTM D4052) kg/L	0.8640	0.8628	0.8668	0.8664	0.8827
VISCOSITY (D445-) cSt @ 40 °C	49.3	65.51	68.3	119	119
cSt @ 100 °C	8.46	10.95	11.3	15.8	15.8
POUR POINT (°C) (D97-)	45	-44	-43	-42	-32
FLASH POINT (°C) (D92-)	238	239	232	241	232
TOTAL BASE NUMBER	8	7.8	7.8	7.9	7.8
COLD CRANK SIM (D5293-) cP@(°C)	5912@-30	5989@-30	5989@-25	6766@-25	8156@-15

SIZES

5W-20	5W-30	10W-30	10W-40	20W-50
1 Litre	1 Litre	1 Litre	1 Litre	1 Litre
5 Litre	5 Litre	5 Litre	5 Litre	5 Litre
18.9 Litre	18.9 Litre	N/A	N/A	N/A
205 Litre	205 Litre	N/A	N/A	205 Litre
Bulk	Bulk	N/A	Bulk	N/A

