

## CANMORE PCG SYNTHETIC BLEND MOTOR OIL

**CANMORE PCG SYNTHETIC BLEND** is formulated with ultra-pure synthetic base oils and superior additive technology.

**CANMORE PCG SYNTHETIC BLEND** not only exceeds the stringent requirements of API SN but also surpasses the stricter limits defined by foreign and domestic automakers for some of their highest performing engines.

Synthetic blends can decrease high temperature volatility burn off that can cause a conventional oil to literally cook and evaporate. The unique detergent package prevents the formation of high temperature deposits and sludge, maintaining engine performance and durability when you need it the most.



### TYPICAL RESULTS

SAE GRADE	5W-20	5W-30	10W-30	10W-40	20W-50
VISCOSITY (D445) cSt @ 40 °c cSt @ 100 °c	48.2 8.5	56.8 10.1	72.8 10.1	96.7 14.5	169.3 18.9
VISCOSITY INDEX (D2270)	154	161	139	155	126
POUR POINT (°c) (D97)	-48	-48	-42	-40	-30
FLASH POINT (°c) (D92)	204	204	204	204	207
VOLATILITY, % LOSS @250 °c (D5800)	12.2	13.8	8.4	8.2	8.2

### SIZES

5W-20	5W-30	10W-30	10W-40	20W-50
1 Litre	1 Litre	1 Litre	1 Litre	1 Litre

### MEETS OR EXCEEDS

- API SN.
- ILSAC GF-5.
- GM6094M 5W-30.
- Ford WSS-M2C94-A, SAE-5W-30.
- Ford WSS-M@C945-A, SAE 5W-20.

### FEATURES & BENEFITS

- Superior cold start up protection.
- Exceptional wear protection.
- Resists degradation due to heat and oxidation.
- High temperature volatility resistance.
- Reduces deposit and sludge formation.

You should always consult your Owners Manual when selecting any lubricant product. Check with your sales Representative for latest product approvals. Please note, these are typical performance indicators and can change without notice.

**CANMORE Petroleum**

205-2415 Holly Lane,  
Ottawa Ontario K1V 7P2, Canada  
www.canmorepetroleum.com

**1-613 800 1214**

